

SM8PS

8" Two-way Full Range Speaker System



Features

- Two-way passive speaker system
- Rotatable horn
- Unique cabinet design
- Water-based paint for environmental purpose

Applications

- Conference Room
- Cafes & Bars
- Lecture Halls
- Music Venues
- Pubs & Restaurants

General Description

The SM8PS is a versatile, two-way passive system, designed to provide exceptional sound reinforcement and stage monitoring from a very compact enclosure. It features a powerful 8" low frequency driver and a 1" exit HF horn loaded dome tweeter mounted on a constant directivity 80° x 50° horn. The HF horn can be rotated to allow the multi-angle enclosure to be used in either its vertical or horizontal orientation. Multiple internal rigging points for ground-support, truss and wall mounting. Pole mount socket, flush handle and Speakon NL4 connectors.

Specifications	
Frequency Response	70Hz-18kHz±3dB,-10dB@65Hz
Drivers	1 x 8" LF driver, 1 x 1" exit HF compression driver
Rated Power (RMS)	200W
Peak Power	800W
Sensitivity (1W/1m)	93dB
Maximum SPL	116dB (continuous), 122dB (peak)
Normal Impedance	8ohms
Dispersion (-6dB)	80° (Horizontal), 50° (Vertical)
Crossover	2.5kHz Passive
Finish	Textured black paint
Protective Grille	Black perforated steel
Connectors	2 x Neutrik Speakon NL4
Fittings	Top hat fitting
Dimensions (W x H x D)	270 x 400 x 270 mm
Weight	11Kg

©2022 Atlas Sound L.P. The Atlas "Circle-A", Soundolier, and Atlas Sound are trademarks of Atlas Sound L.P. IED is a Registered Trademark of Innovative Electronic Designs LLC. All rights reserved. All other Trademarks are property of their respective owners. No endorsement is implied. Due to continual product development, specifications are subject to change without notice. ATSO06880 RevA 7/22